

MULTI PARA MONITOR

CMS 8000(12.1")



NIBP

- +Method Oscillometry
- +Modes Manual / Auto / Continuous
- +Auto Measure time Adjustable
- +Measurement range 10-270mmHg

ECG

- +Lead Mode 3-lead Or 5-lead
- +Lead Selection I, II, III, avR, avL, avF, v
- +Heart rate range Adult: 15-300bpm, pediatric / Neonatal 15-300bpm
- +ECG waveform 2 channels
- +Accuracy ± 1 bpm or ± 1 %, Whichever is greater
- +S-T segment detection: Measurement range 0.2mv-2.0mv

Specification

- +Alarm Yes, audible and visual alarm, alarm events review
- +High resolution 12.1" or 8.4" color TFT display
- +Lightweight, compact and portable
- +ECG, SPO₂, NIBP, RESP, 2-TEMP PR
- +Built-in rechargeable lithium battery
- +ECG waveforms of 7-leads display on the same screen
- +72-hours graphic and tabular trends of all parameters
- +72 alarm events of all parameters recall
- +32 seconds full-disclosure waveform review
- +Suitable for adult, pediatric and neonatal patient

SPO₂

- Measurement range 0-100%
- Accuracy 70-100%, $\pm 2\%$ 0-69%, unspecified

Pulse Rate

- Range 20-254pm
- Accuracy ± 3 bpm

Respiration

- Method RA-LL impedance
- Range Adult: 0-120rpm; pediatric/neonatal: 0-15rpm
- Apnea alarm yes

Temperature

- Range 0-50 °C
- Accuracy ± 0.1 °C
- Channel Dual - channel

Optional

- Nellcore SPO₂, ETCO₂, IBP, Printer & Networking



EtCO₂ (SIDE STREAM)Module



EtCO₂ (MAIN STREAM) Module



IBP Module



Reusable IBP Extension Cable



Disposable IBP Kit



We support service...